

Ankerbolts ETA Option 1



Fire Resistant



Ankerbolts ETA Option 1									
Part Number	Drill Diameter	Thread Diameter	Anchor Length	Maximum Fixture Thickness	Fixture Clearance Hole	Minimum Hole Depth	Minimum Structure Thickness	Drive Socket Size	Tightening Torque Nm
JAB08/10075ETA	8	10	80	5	12	90	120	15 a/f	40
JAB08/10100ETA			100	25					
JAB08/10130ETA			130	55					
JAB08/10150ETA			150	75					
JAB10/12100ETA	10	12	100	15	14	100	125	17 a/f	60
JAB10/12130ETA			130	45					
JAB10/12150ETA			150	65					
JAB12/14100ETA	12	14	100	5	16	110	140	19 a/f	80
JAB12/14130ETA			130	35					
JAB12/14150ETA			150	55					
JAB12/14200ETA			200	105					
JAB14/16150ETA	14	16	150	40	18	130	170	24a/f	90

Suitable For Use In Cracked And Non Cracked Concrete Range Between C20/25 And C50/60
Hollow Concrete Planks - Solid Brick - Concrete Blocks - Natural Stone

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY