

## Csk Head Heavy Duty Anchor ETA Option 1 Approved



Fire Resistant



Csk Head Heavy Duty Anchor ERA Option 1 Approved											
Part Number	Thread Diameter	Anchor Length	Drill Hole Diameter Size	Maximum Fixing Thickness	Fixture Clearance Hole	Hed Diameter	Embedment Depth	Minimum Hole Depth	Structure Thickness	Hexagon Drive	Installation Yorque
	mm	mm		mm	mm	mm	mm	mm	mm	mm	Nm
SLSK10/10	6	70	10	10	12	16.8	60	65	105	4	15
SLSK10/25		85		25							
SLSK10/45		100		40							
SLSK12/10	8	80	12	10	14	20.5	70	80	125	5	30
SLSK12/25		95		25							
SLSK12/50		120		40							
SLSK15/10	10	100	15	10	17	24.5	85	95	145	6	50
SLSK15/25		110		25							
SLSK15/50		135		50							
SLSK18/20	12	115	18	20	20	29.5	95	105	165	8	80
SLSK18/40		135		40							


Zinc Plated Torque Controlled Through Fixing Suitable For Use In Cracked And Non Cracked Concrete  
Range Between C20/25 And C50/60



Drill Correct Diameter  
Hole To Correct Depth



Clean Hole By Brushing  
And Blowing To Remove  
All Dust And Debris



Insert  
Assembled  
Anchor Into  
Concrete



Tighten With Torque  
Wrench To  
Recommended Torque

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY