

HSS M42 Cobalt (Constant Pitch) Holesaws



Hole Saw Diameter	Thread Mount (Inches)	Saw Depth
16m/m	1/2 x 20	32
17m/m	1/2 x 20	32
20m/m	1/2 x 20	32
22m/m	1/2 x 20	32
24m/m	1/2 x 20	32
25m/m	1/2 x 20	32
27m/m	1/2 x 20	32
30m/m	1/2 x 20	32
32m/m	5/8 x 18	32
35m/m	5/8 x 18	32
37m/m	5/8 x 18	32
40m/m	5/8 x 18	31
41m/m	5/8 x 18	32
43m/m	5/8 x 18	32
46m/m	5/8 x 18	32
48m/m	5/8 x 18	32
51m/m	5/8 x 18	32



Hole Saw Diameter	Thread Mount (Inches)	Saw Depth
60m/m	5/8 x 20	32
64m/m	5/8 x 20	32
68m/m	5/8 x 20	32
70m/m	5/8 x 20	32
75m/m	5/8 x 20	32
76m/m	5/8 x 20	32
79m/m	5/8 x 20	32
86m/m	5/8 x 20	32
89m/m	5/8 x 20	32
95m/m	5/8 x 20	32
92m/m	5/8 x 20	32
102m/m	5/8 x 20	32
108m/m	5/8 x 20	32
160m/m	5/8 x 20	32
165m/m	5/8 x 20	32
210m/m	5/8 x 20	32

Constant Pitch Ensures Smooth Cutting And Less Chatter When Drilling Metal Particularly Thin Sheet

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE PURPOSES ONLY