

Headed Brass Expansion Self Locking Inersts



| Headed Brass Expansion Self Locking Inserts | | | | | | | | |
|---|------|-------|------|------|------|------|------|------|
| Internal Thread | M2* | M2.5* | M3 | M3.5 | M4 | M5 | M6 | M8* |
| C | 4.8 | 5.5 | 5.5 | 6.4 | 7.1 | 7.9 | 9.5 | 11.1 |
| B-Minimum | 0.43 | 0.51 | 0.51 | 0.66 | 0.82 | 0.99 | 1.25 | 1.25 |
| Length | 3.9 | 4.7 | 4.7 | 6.3 | 7.9 | 9.4 | 12.6 | 12.6 |
| Min. Wall Thk. | 2.4 | 3.2 | 3.2 | 3.6 | 4.0 | 4.8 | 8.0 | 9.6 |
| Recommended | 3.2 | 4.0 | 4.0 | 4.8 | 5.6 | 6.4 | 8.0 | 7.0 |
| Hole | To | To | To | To | To | To | To | To |
| Size | 3.3 | 4.1 | 4.1 | 4.9 | 5.7 | 6.5 | 8.1 | 7.1 |

*Non Preferred Availability On Request
Minimum Batch Quantities May Apply *

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY