

Hexagon Bolt Heavy Duty Anchor ET Option 1 Approved



Fire Resistant



Hexagon Bolt Heavy Duty Anchor ET Option 1 Approved										
Part Number	Thread Diameter mm	Anchor Length mm	Drill Hole Diam mm	Maximum Fixture Thickness mm	Fixture Clearance Hole mm	Embedment Depth mm	Minimum Hole Depth mm	Structure Thickness mm	Bolt Across Flats mm	Installation Torque Nm
JHD0610	6	75	10	10	12	60	65	105	10	15
JHD0630		95		30						
JHD0650		115		50						
JHD0810	8	87	12	10	14	70	80	125	13	30
JHD0830		107		30						
JHD0850		127		50						
JHD1015	10	108	15	15	17	85	95	145	17	50
JHD1025		118		25						
JHD1045		138		45						
JHD1210	12	117	18	10	20	95	105	165	19	80
JHD1220		127		20						
JHD1240		147		40						
JHD1270		177		70						
JHD1610	16	132	24	10	26	120	130	205	24	160
JHD1620		152		20						
JHD1650		182		50						
JHD2030	20	192	28	30	30	150	160	255	30	280
JHD2060		222		60						

Zinc Plated Torque Controlled Through Fixing Suitable For Use In Cracked And Non-Cracked Concrete
Range Between C20/25 And C50/60



1
Drill Correct Diameter
Hole To Correct Depth



2
Clean Hole By Brushing Insert Assembled
And Blowing To Remove All Dust And Debris



3
Tighten With Torque
Wrench To
Recommended Torque



INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY