Sleeve Anchor Hex Nut S.S.

Non-Cracked concrete (Loads are not applicable to anchors with reduced embedment depth)

Performance Data (C20/25 Concrete)											
Outside Diam	Characteristic Resistance		Design Resistance		Recommended Resistance		Design Spacing	Design Edge Distance			
mm	k	N	k	N	k	N	mm	m	m		
	Tensile	Shear	Tensile	Shear	Tensile	Shear	Tensile & Shear	Tensile	Shear		
6	5.4	3.5	3.0	2.8	2.1	2.0	50	40	35		
8	6.6	4.0	3.6	3.1	2.5	2.2	55	45	40		
10	10.2	7.3	5.6	5.8	4.0	4.1	100	70	60		
12	12.6	11.6	6.9	9.2	5.0	6.5	115	80	85		

Shear Loads towards a free edge are for single anchors where Spacing ≥ 3 x Edge Distance

For variations in structure thickness, reduced spacing and edge calculations download the free Anchor Calculation Program from www.jcpfixings.co.uk

Influence of concrete strength Not applicable with sleeve anchors

Solid Brickwork (Loads are not applicable to anchors with reduced embedment depth)

				Perfe	ormance D	ata (20 N/	mm²)			
Outside Diameter	neter Resistance		Design Resistance kN		Recommended Resistance kN		Recommended Spacing	Recommended Edge Distance mm		Tightening Torque Nm
mm							mm			
	Tensile	Shear	Tensile	Shear	Tensile	Shear	Tensile & Shear	Tensile	Shear	
6	1.6	1.6	0.7	1.0	0.5	0.7	80	40	50	6
8	2.3	3.6	1.1	2.4	0.8	1.7	90	45	60	8
10	3.1	7.4	1.5	4.9	1.1	3.5	110	55	70	16
12	4.4	11.4	2.1	7.6	1.5	5.4	Only 1 fixing per brick is recommended			25

Solid Concrete Blocks (Loads are not applicable to anchors with reduced embedment depth)

				Perf	ormance D	ata (7 N/r	nm²)			
Outside Diameter	Characteristic Resistance kN		Design Resistance kN		Recommended Resistance kN		Recommended Spacing	Recommended Edge Distance mm		Tightening Torque Nm
mm							mm			
	Tensile	Shear	Tensile	Shear	Tensile	Shear	Tensile & Shear	Tensile	Shear	
6	1.3	0.6	0.6	0.4	0.4	0.3	80	40	50	5
8	1.5	2.1	0.7	1.4	0.5	1.0	90	45	60	6
10	2.3	4.4	1.1	2.9	0.8	2.0	110	55	70	12
12	2.9	6.7	1.4	4.4	1.0	3.1	120	60	80	20

Due to the variable nature of bricks and concrete blocks these figures are for guidance only