

Hook And Eye Ankerbolts



Hook Bolts						
Part Number	Outside Diameter	Drill Diameter	Hook Diameter	Overall Length	Thread Length	Min. Hole Depth
JAB06/08050HOOK	8m/m	6m/m	13m/m	90m/m	50m/m	40m/m
JAB08/10055HOOK	10m/m	8m/m	13m/m	90m/m	55m/m	45m/m



Eye Bolt						
Part Number	Outside Diameter	Drill Diameter	Eye Diameter	Overall Length	Thread Length	Min. Hole Depth
JAB06/08050EYE	8m/m	6m/m	13m/m	90m/m	50m/m	40m/m
JAB08/10055EYE	10m/m	8m/m	15m/m	90m/m	55m/m	45m/m

Performance Data (C20/25 Concrete)					
Drill Diameter	Characteristic Resistance	Design Resistance	Recommended Resistance	Spacing	Edge Distance
6m/m	6 kn	3.3 kn	2.3 kn	65m/m	55m/m
8m/m	9 kn	4.9 kn	3.5 kn	80m/m	75m/m

(Loads Are In Any Direction)

**Hook And Eye Bolts Are Only To Be Used For Static Loads
That Are NOT To Be Used For Safety Harness Anchorage Points, Dynamic Loads Or As Lifting Eyes**

Material: Hardened Steel Self Tapping Screw
FOR Use In Concrete, Solid Brick and Hard Natural Stone

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY