

Injection Resin

JFV300SF



Water Regulations
Advisory Service



WRAS Listing Number
1605427

Option 1
Cracked Concrete



Vol: 410ml

ETA15/0704

Vinylester Resin

Is A Two Part Grey Resin (10:1)
Suitable For Use In Vast Majority
Base Materials. It Can Be Used
For Installing Threaded Studs
Rebar, Threaded Internal Sockets
For Structural Applications

Base Material

Concrete C20/25 To Concrete C50/60
Cracked / Non Cracked Concrete
Dry / Wet / Flooded Holes
Solid Brickwork-Concrete Block
Natural Stone

Features

Expansion Free - High Performance
Close Spacing And Edge Distance
Can Be Used In Contact With
Portable (Drinking) Water

JFV380SF



Option 1
Cracked Concrete



ETA15/0704

Vol: 410ml

Vinylester Resin

Is A Two Part Grey Resin (10:1)
Suitable For Use In Vast Majority
Base Materials. It Can Be Used
For Installing Threaded Studs
Rebar, Threaded Internal Sockets
For Structural Applications

Base Material

Concrete C20/25 To Concrete C50/60
Cracked / Non Cracked Concrete
Dry / Wet / Flooded Holes
Solid Brickwork-Concrete Block
Natural Stone

Features

Expansion Free - High Performance
Close Spacing And Edge Distance
Can Be Used In Contact With
Portable (Drinking) Water

JFEA1410SF



Option 1
Cracked Concrete



ETA15/0704

Vol: 410ml

Vinylester Resin

Is A Two Part Grey Resin (10:1)
Suitable For Use In Temperatures
Down To -10 Degree C Or As A
Fast Cure Resin In Warmer
Temperatures. It Can Be Used
For Installing Threaded Studs
Rebar, Threaded Internal Sockets
For Structural Applications

Base Material

Concrete C20/25 To Concrete C50/60
Cracked / Non Cracked Concrete
Dry / Wet / Flooded Holes
Solid Brickwork-Concrete Block
Natural Stone

Features

Fast Cure Resin - Winter Grade
Expansion Free - High Performance
Close Spacing And Edge Distance

FURTHER DATA SHEET ARE AVAILABLE ON REQUEST