

## Injection Resin

**JFEA300SF**



Vol: 300ml

Option 7  
Non-Cracked Concrete  
  
ETA16/0622

**Polyester Styrene Free Resin**  
Is A Two Part Grey Resin (10:1)  
Suitable For Use In Vast Majority  
Of Base Materials. It Can Be Used  
For Installing Threaded Studs  
Rebar And Threaded Internal Sockets  
For Structural Applications

**Base Materials**  
Concrete C20/25 To C50/60  
Non Cracked Concrete  
Dry / Wet / Flooded Holes  
Solid Brickwork - Concrete Block  
Hollow Base Materials - Natural Stone

**Features**  
Expansion Free - High Performance  
Close Spacing And Edge Distance

**JF380P**



Vol.410ml

Option 7  
Non-Cracked Concrete  
  
ETA13-0781

**Polyester Resin**  
Is A Two Part Grey Resin (10:1)  
Suitable For For Use In Vast Majority  
Of Base Materials. It Can Be Used For  
Installing Threaded Studs, Rebar And Internal  
Threaded Sockets For Structural Applications


**Base Materials**  
Concrete C20/25 To C50/60  
Non Cracked Concrete  
Dry / Wet / Flooded Holes  
Solid Brickwork - Concrete Block  
Holow Base Materials - Natural Stone

**Features**  
Expansion Free - High Performance  
Close Spacing And Edge Distance

**JF380PSF**



Vol.410ml

Option 7  
Non-Cracked Concrete  
  
ETA13/0782

**Polyester Styrene Free Resin**  
Is A Two Part Grey Resin (10:1)  
Suitable For Use In Vast Majority  
Of Base Materials. It Can Be Used  
For Installing Threaded Studs  
Rebar And Internal Threaded Sockets  
For Stuctural Applications

**Base Material**  
Concrete C20/25 To C50/60  
Non Cracked Concrete  
Dry / Wet / Flooded Holes  
Solid Brickwork -Concrete Block  
Hollow Base Materials - Natural Stone

**Features**  
Expansion Free - High Performance  
Close Spacing And Edge Distance

**FURTHER DATA SHEETS ARE AVAILABLE ON REQUEST**