




TIMCO Multi-Fix™

POLYESTER RESIN

Version: 07/07/2014

Features and Benefits

- Good bond strength with High load resistance
- Used with all grades of threaded rod
- Used in concrete and masonry
- Fast gelling and curing
- Used in dry and wet conditions
- Also suitable as a filler for gap and crack filling
- Economical fixing resin
- Extremely versatile
- Close edge distance and small spacing
- Manual cleaning up to 20mm diameter and embedment depths of 240mm
- Independently tested and approved (ITB Approval / Socotec Approval)



Contents

- PAGE 1 - Features and Benefits
- PAGE 2 - Loads, Edge and Spacings based on Characteristic bond strengths
Showing steel failure
- PAGE 3 - Material properties for threaded rods and rebar
- PAGE 4 - Tension Edge and Spacing reduction factors
- PAGE 5 - Curing Time / Temperature Range
- PAGE 6 - Installation parameters: drilling hole cleaning and installation Hollow Wall.
- PAGE 7 - Installation parameters: drilling hole cleaning and installation.

Shelf Life and Storage

This product should be stored between +5°C & +25°C.
The Shelf life of the product is 12 months from the manufacture date.

IMPORTANT The information and data given is based on our own experience, research and testing and is believed to be reliable and accurate. However, as we cannot know the varied uses to which its products may be applied, or the methods of application used, no warranty as to the fitness or suitability of its products is given or implied. It is the users responsibility to determine suitability of use. For further information please contact Our Technical Department.