


Pre-Load Wave Washers



Pre-Load Wave Washers													
Housing Diameter mm	A (mm)	B (mm)	Material Thk. S	C approx	Number Of Waves	Bearing Reference	Housing Diameter mm	A (mm)	B (mm)	Material Thk. S	C approx	Number Of Waves	Bearing Reference
10	9.5	4.5	0.20	1.1	2	623	75	74.5	62.0	0.60	7.1	3	6009
13	12.5	7.5	0.20	1.4	2	624	80	79.5	63.5	0.60	5.2	3	6010-6208-6307-6405
16	15.5	10.5	0.15	1.2	3	625-634	80	78.5	63.5	0.60	5.8	3	
16	15.5	10.5	0.15	1.3	3		85	84.5	67.0	0.60	6.8	3	6209
17	16.5	11.5	0.20	1.4	3		90	89.5	72.0	0.60	6.0	3	6001-6210-6308-6406
19	18.5	13.0	0.20	1.5	3	607-626-635	90	94.5	75.5	0.70	7.2	3	
21	20.5	15.0	0.20	1.8	3		90	89.5	72.0	0.70	6.4	3	
22	21.5	16.0	0.20	2.1	3	608-627	95	94.5	75.5	0.70	7.2	3	6012
24	23.5	17.0	0.20	2.2	3	609	100	99.5	80.5	0.70	6.9	3	6013-6211-6309-6407
26	25.5	19.0	0.30	2.0	3	6000-629	105	104.5	84.5	0.80	6.6	3	
26	25.5	19.0	0.30	2.1	3		110	109.5	90.5	0.80	7.0	3	6014-6212-6310-6408
28	27.5	21.0	0.30	2.2	3	6001	115	114.5	95.5	0.80	10.0	3	6015
28	27.5	21.0	0.30	2.5	3	6001	117	116.5	97.5	0.80	9.0	3	
29	29.5	23.0	0.30	2.5	3	6200	120	119.5	100.5	0.80	10.0	3	6213-6311
32	31.5	25.0	0.30	2.8	3	6002-6201	125	124.5	105.5	0.80	13.0	3	6016-6214
32	31.5	25.0	0.30	3.1	3		127	126.5	107.5	0.80	14.0	3	
32	31.5	25.0	0.30	3.5	3		130	129.5	110.5	0.80	13.0	3	6017-6215-6312-6410
35	34.5	28.0	0.40	2.7	3	6003-6202-6300	130	129.5	110.5	1.00	10.0	3	
35	34.5	28.0	0.40	2.9	3		135	134.5	114.0	1.00	10.7	3	
37	36.5	30.0	0.40	2.7	3	6301	137	136.5	116.0	1.00	9.3	3	
37	36.5	30.0	0.40	2.9	3		140	139.5	119.0	1.00	9.8	3	6018-6216-6313-6411
38	37.5	31.0	0.40	3.2	3		145	144.5	124.0	1.00	14.5	3	6019
40	39.5	33.0	0.40	3.6	3	6203	150	149.5	129.0	1.00	11.0	3	6020-6218-6314-6412
42	41.5	33.5	0.40	3.2	3	6004-6302	157	156.5	136.0	1.00	15.5	3	
42	41.5	33.5	0.40	3.6	3		160	159.5	139.0	1.00	16.0	3	6021-6218-6315-6413
44	43.5	35.5	0.40	3.7	3		170	169.5	149.0	1.20	12.0	3	6022-6219-6316
47	46.5	38.5	0.50	3.0	3	6005-6204-6303	180	179.5	159.0	1.20	14.0	3	6024-6220-6317-6414
47	46.5	38.5	0.50	3.1	3		190	189.5	16.0	3.00	16.0	3	6221-6318-6415
47	46.5	38.5	0.50	3.5	3		200	199.5	177.0	1.20	11.0	3	6222-6319-6416
52	51.5	42.0	0.50	3.3	3	6205-6304	210	209.5	185.5	1.20	11.5	3	6223-6417
52	51.5	42.0	0.50	3.8	3		215	214.5	190.5	1.20	12.2	3	6224-6320
55	54.5	43.5	0.50	4.1	3	6006	220	219.5	195.5	2.00	7.4	3	
62	61.5	50.5	0.50	4.0	3	6007-6206-6305-6403	225	224.5	200.5	2.00	10.7	3	6321-6418
62	61.5	50.5	0.50	4.9	3		230	229.5	205.0	2.00	10.8	3	6226
62	61.5	50.5	0.60	3.9	3		240	239.5	214.0	2.00	12.2	3	6322
62	61.5	50.5	0.60	4.4	3		250	249.5	224.0	2.00	17.0	3	6228-6323
68	67.5	55.0	0.60	5.0	3	6008	260	259.5	234.0	2.00	18.2	3	6229-6324
70	69.5	57.0	0.60	5.0	3		270	269.5	242.0	2.00	26.7	3	6230
72	71.5	59.0	0.60	4.8	3	6207-6306-6404	280	279.5	252.0	2.00	23.5	3	6323
72	71.5	59.0	0.60	5.2	3								

For Pre-Loading Bearings In Electric Motors

Bearing Installed In The Bearing Housing And Works By Maintaining A Force On The Outer Race Of The Ball Bearing Ensuring Smooth And Quiet Running Resulting In Extended Life

Material

High Carbon Spring Steel - Self Colour

Stainless Steel - Beryllium Copper Etc On Request

INFORMATION AND DRAWINGS PROVIDED ARE REFERENCE ONLY