



Quicklock External Fixing Washers



Quicklock External Fixing Washers							
Shaft Size mm	DE Outside Diameter mm	D1 Outside Diameter +0.05mm	T Thickness mm	L Shaft Face To Retained Face	Axial Load N	Material And Finish	
0.8mm	4.0	0.65	0.2mm	1.5mm	—	Carbon Steel	
1.0mm		0.85			100		
1.2mm		1.05			100		
1.5mm	5.0	1.30	0.2mm	2.0mm	170		
2.0mm	7.0	1.80			350		
2.5mm	8.5	2.30	0.3mm	2.5mm	600		Hardened And Tempered
3.0mm	10.5	2.80			1000		
3.5mm	11.0	3.30			1100		
4.0mm	12.0	3.75	0.4mm	3.0mm	1200		Finish: Phosphate And Oil
4.5mm	13.0	4.25			1300		
5.0mm	14.0	4.75		3.5mm	1400		
5.5mm	14.0	5.25			1300		
6.0mm	16.0	5.75		3.5mm	1600		
6.35mm	14.0	6.00			1300		
7.0mm	17.0	6.70		3.5mm	2700		
8.0mm	18.0	7.70			3000		
9.0mm	19.0	8.65	3500				
10.0mm	20.0	9.65					

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY