

Self Clinch Floating Nuts



Thread And Pitch	Material Code	Min Sheet Thk	S Max	C Max	D Max	B + 0.4 - 0.4	H Max Non Locking	H Max Locking	Hole Size In Panel + 0.08	Min C/L To Edge Of Panel
M3 x 0.5	1	1.0	0.97	7.35	7.37	9.14	3.31	4.85	7.37	7.62
	2	1.4	1.38							
M4 x 0.7	1	1.0	0.97	9.33	9.28	11.18	3.31	5.34	9.35	8.64
	2	1.4	1.38							
M5 x 0.8	1	1.0	0.97	10.29	10.29	11.94	4.32	6.86	10.31	9.14
	2	1.4	1.38							
M6 x 1.0	2	1.4	1.38	3.06?	12.96	15.24	5.34	7.88	13.1	10.67

Material
Carbon Steel Electro Zinc Plated 300 Series Stainless Steel A2 Maximum Hardness Of Parent Material On Steel & Stainless Steel Parts 70 HRB

Ordering Example
M3-2-Z- (Floating Nut 1.0mm Minimum Sheet Thickness) M4-2 Stainless Steel (Floating Nut 1.4mm Minimum Sheet Thickness)
M5-1-Z1 (Locking Floating Nut 1.0mm Minimum Sheet Thickness) M3-2 Stainless Steel (Locking Floating Nut 1.4mm Min. Sheet Thk)

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY