

Self Clinch Nuts



Self Clinch Nuts							
Thread And Pitch	Material Code	S Maximum	Min Sheet Thickness	Hole Size In Sheet + 0.08 - 0.00	C Maximum	D + 0.2	H + 0.1
M2 x 0.4	0	0.76	0.8	4.25	4.22	6.3	1.5
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
M2.5 x 0.45	0	0.76	0.8	4.25	4.22	6.3	1.5
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
M3 x 0.5	0	0.76	0.8	4.25	4.22	6.3	1.5
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
3.5M3 x 0.5	1	0.97	1.0	4.75	4.73	7.1	1.5
	2	1.37	1.4				
M3.5 x 0.6	0	0.76	0.8	5.4	4.73	7.1	1.5
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
M4 x 0.7	0	0.76	0.8	5.4	5.38	7.9	2.0
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
M5 x 0.8	0	0.76	0.8	6.4	6.38	8.7	2.0
	1	0.97	1.0				
	2	1.37	1.4				
	3	2.21	2.3				
M6 x 1.0	1	1.37	1.4	8.75	8.72	11.05	4.08
	2	2.21	2.3				
	3	3.05	3.2				
	1	1.37	1.4				
M8 x 1.25	2	2.21	2.3	10.5	10.44	12.65	5.47
	3	3.05	3.2				
	1	2.21	2.3				
	2	3.05	3.2				
M10 x 1.5	3	6.00	6.4	14.0	13.94	17.35	7.48

Material	Finish	Used In Rockwell Hardness	
Carbon Steel	Electro Zinc Plated	Steel	8 -80 Maximum
Stainless Steel 300 Series		Stainless Steel 8-70 Maximum	

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY