

Self Cutting Blind Threaded Inserts



Self Cutting Blind Threaded Inserts										
Internal Thrad	M2	M3	M4	M5	M6	M8	M10	M12	M16	M20
Length	7	8	9	10	12	15	20	25	35	40
Outside Diameter	4	5	6	8	9	12	14	16	25	30
Recommended Hole Size	3.2	3.9	4.8	6.6	7.4	9.7	11.5	13.6	22.0	27.0
	3.7	4.7	5.6	7.6	8.6	7.6	13.6	15.5	24.0	29.0

Material : 303 Stainless Steel AND 316 Marine Grade Stainless Steel

* All Recommended Hole Sizes Are Advisory And Should be Treated As Such
 For Woods Such As Oak And Soft Plastic A Preparartion Hole Size Towards The End Of The Rnages Is Reccomended
 Allowing The Insert To Cut Into With Relative Ease
 For Larger Inserts Requiring More Force To Insert The Following Considerations Are Reccomended
 Consider How Much And Direction The Load Will Be Going When The Insert Is Installed
 If The Load Is Going To Be Pulling On The insert Keep The Hole As Small As Possible In Order To Give The External Thread
 More Grip In The Wood To Prevent Pullout
 If The Load Is Lateral The Hole Size Can Be Increased As The Load Will Be Acting Against The Side Of The Insert
 Pull Out Will Be Less Of An Issue And The Insert Will Be Easier To Insert

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY