

Throughbolts A4-316 ETA Option 7 Uncracked Concrete



Fire Resistant



Throughbolts A4-316 ETA Option 7 Uncracked Concrete									
Part Number	Anchor Length And Dia	Hole Diameter mm	Fixture Clearance Hole	Max . Fixing Thickness		Min. Embedment Depth		Minimum Hole Depth	
				Standard Embedment mm	Reduced Embedment mm	Standard Embedment mm	Reduced Embedment mm	Standard Embedment mm	Reduced Embedment mm
TSS06040	6 x 40	6	7	—	5	—	27	—	35
TSS06065	6 x 67	6	7	10	20	49	39	55	45
TSS08050	8 x 50	8	9	—	5	—	35	—	45
TSS08075	8 x 75			10	19	56	47	65	55
TSS08095	8 x 95			30	39				
TSS08120	8 x 120			55	64				
TSS10060	10 x 60			10	12	—	10	—	40
TSS10080	10 x 85	10	16			62	56	70	65
TSS10100	10 x 105	30	36						
TSS10125	10 x 125	50	56						
TSS10175	10 x 175	100	106						
TSS12085	12 x 95	12	14	—	14	81	65	90	75
TSS12100	12 x 105			10	25				
TSS12115	12 x 115			20	35				
TSS12145	12 x 145			50	65				
TSS12200	12 x 200			105	120				
TSS16110	16 x 115	16	18	—	14	99	83	110	95
TSS16125	16 x 130			10	26				
TSS16150	16 x 150			30	46				
TSS16175	16 x 180			60	76				
TSS20170	20 x 180	20	22	35	57	121	99	130	110
TSS20220	20 x 240			95	117				

Grade A4-316 Stainless Steel Torque Controlled Throughbolt Suitable For Use In Non-Cracked Concrete
Range Between C20/25 And C50/60



Drill correct Diameter Hole To Correct Depth



Clean Hole By Brushing And Blowing To Remove All Dust And Debris



Insert Assembled Throughbolt Through Fixture Into Concrete



Tighten With Torque Wrench To Recommended Torque Wrench

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY