

Twist Knot Wire Brushes And Wheel

Twist Knott Steel Wire Bevel Brush



Part Numbers
100 TBT
Diameter 100 m/m
Arbor M14
Wire Thickness 0.5m/m

MAX RPM 12,500

For Use On Angle Grinders
When Clraning Metal, Wood
And Masonry Surfaces.
Twist Brush Is Ideal For
Aggressive Removal Of Paint
Rust, Rubber, Concrete And Dirt
And Is Ideal For Accessing Awkward
Areas

Twist Knot Steel Wire Brush



Part Number 115 TWT
Diameter 115m/m
Arbor M14
Wire Thickness 0.5m/m

MAX RPM 12,500

For Use On Angle Grinders
When Cleaning Metal, Masonry
And Wood Surfaces.
The Twist Brush Is Ideal For
Aggressive Removal Of Paint
Rubber, Concrete Or Dirt
Ideal For Accessing Awkward
Areas

Twist Knot Stainless Steel Bevel Wire Brush



Part Numbers
100 TBTSS
Diameter 100m/m
Arbor M14
Wire Thickness 0.5m/m

MAX RPM 12,500

For Use On Angle Grinders
The Twist Brush Is Ideal
For Aggressive Removal Of
Paint, Rust, Rubber And Concrete
Or Dirt Without Contaminating
The Base Material
Ideal For Accessing Awkward
Areas



Part Number
115 TWTSS
Diameter 115m/m
Arbor M14
Wire Thickness 0.5m/m

MAX RPM 12,500

For Use On Angle Grinders
The Twist Brush Is Ideal
For Aggressive Removal Of
Paint, Rust, Rubber, Concrete
Or Dirt And Reduces
Contamination Of The Base
Material
Ideal For Accessing Awkward Areas

Steel Wire Wheel Brush C/W Plastic Reducing Bushes

Diameters 150 And 200m/m



Part Numbers
150 HWC
200 HWC
Arbor 32m/m
Wire Thickness 0.3m/m

MAX RPM 6,000

For Use On A Bench Grinder For Cleaning And Polishing Metal Surfaces
Crimped Wire Ideal For Lightly Reoving Loose Paint, Rust And Dirt Without
Scarring The Base Material

FOR PERSONAL SAFETY PLEASE DO NOT EXCEED THE MAXIMUM RPM